



PREDATOR +

Eddy Current Instrument

Meets IP65; Rain:
MIL-STD-810G, 506.4
Sealing Dust &
MIL-STD 810G, 506.5 IV
Drop/Shock



“PREDATOR” USB Eddy Current Instrument:

- Frequency Range: 2 Hz-14 MHz
- Gain: 0-100 in 1 step increments
- Probe Drive: LOW, MID & HIGH
- Rotation: 0°-359° in 1° increments
- Impedance (Lissajous) Display
- Separate Null and Position Controls
- Battery Life: 6 Hours on two 10400mAh, 7.4V, 77Wh, Hot Swappable, High Capacity Lithium Ion Batteries
- Use either Differential or Reflection Probes
- Digitizing Rate: 7,800 samples/sec maximum
- USB Plug & Play
- Display: 7.0” Diagonal Widescreen, 1024 (W) x 600 (H) (WSVGA) Color TFT
- 10 x 10 Graticule Display Grid
- Size: 8.8” W x 5.7” H x 1.56” D
- Weight: 4.5 Pounds w/High Capacity Batteries

VM Products, Inc.

*Specialists in Eddy Current Probes,
Reference Standards, Applications,
Research & Development*



P.O. Box 44926, Tacoma, WA 98448

Tel: (253) 841-2939 / Fax: (253) 841-3016

www.vmproducts.net * sales@vmproducts.net