


## GE Transducers Available for Vantage Systems




Center Frequency: 6.5 MHz Bandwith: 85% Number of elements: 256 Pitch: 0.20mm Elevation Focus: 22 mm Elevation aperture: 5.0 mm

MUX: Yes

Compatibility Vantage 256, 128, 64LE







GE 4C-D Curved Linear Array



Center Frequency: 3.2 MHz
Bandwith: 70% Number of elements: 128
Pitch: 0.478mm Elevation Focus: 67 mm
Elevation aperture: 13 mm
Radius of Curvature: 60.0
Compatibility: Vantage 256, 128, 64*LE* 






GE C1-6-D
Curved Linear Array



Center Frequency: 3.4 MHz Bandwith: 95% Number of Elements: 192 Pitch: 0.350mm Elevation Focus: 66 mm

> Elevation Aperture: 11.5 mm Radius of Curvature: 56.8 Compatibility: Vantage 256







GE IC5-9-D Intracavitary Curved Linear Array



Center Frequency: 5.8 MHz Bandwith: 75% Number of elements: 192 Pitch: 0.138mm Elevation Focus: 35 mm

> Elevation aperture: 6.0 mm Radius of Curvature: 10.1 mm Compatibility: Vantage 256





GE M5Sc-D Phased Array



Center Frequency: 2.8 MHz

Bandwith: 90% Number of elements: 80 x 3

Pitch: 0.23 mm Elevation Focus: 77 mm

**Elevation aperture:** 13.0 mm **Compatibility:** Vantage 256

